
tigated in several laboratories worldwide. One nonlinear optical effect which appears promising for device application is optical limiting of nanosecond duration visible laser pulses in C₆₀ solutions. Experimental and theoretical study of this phenomenon at CAT has led to a better understanding of the underlying physical mechanism. In C60, absorption in the visible region results in excitation of the molecules to the long-lived triplet state. The absorption from this level is much stronger than that from the ground state and earlier it was believed that this 'reverse saturable absorption' is responsible for the observed limiting. The work at CAT has shown that this mechanism cannot fully account for the experimental observations and, in fact, a stronger role in the limiting action is played by induced scattering in C60 solutions. The scattering has been found to be laser fluence dependent and appears to be of thermal origin. Furthermore, nonlinear refraction in C60 solution, resulting from refractive index changes which can be due to heating and population transfer to the triplet state, has been shown to be important.

High resolution FIR and IR spectroscopy

A torsion-rotation-distorsion interaction Hamiltonian has been developed for symmetric and slightly asymmetric molecules capable of hindered internal rotation in a three fold potential barrier. The model has been successfully applied to the case of methyl alcohol, which is a slightly asymmetric molecule and is the best source of optically pumped FIR laser lines. The analysis has resulted in the interpretation of torsion-rotation and vibration-torsionrotation high resolution Fourier transform spectra of methanol and some of its isotopic derivatives, e.g., ¹³CH₃OH, CD₃OH, ¹³CD₃OH, and CH₃OD. For the parent species the IR analysis resulted in the assignments and predictions of many optically pumped FIR laser lines. Of particular importance is the identification and prediction of FIR laser lines from the highly excited torsional states in the C-O stretch state. Using accurate combination loops the frequencies of the emission lines obtained to at



Sealed-off nitrogen laser developed at CAT.

least an order of magnitude better accuracy than can be obtained from direct wavelength measurements. This study of the FIR absorption spectrum (20 - 350 cm⁻¹) has resulted in an atlas of about 20,000 precise line positions with an accuracy of about 5 MHz. This atlas has been identified by the Journal of Molecular Spectroscopy as a secondary wavenumber standard in the FIR region.

The study on the other isotopes of methanol has made it possible to interpret their laser Stark spectra and double resonance spectra. A Coriolis interaction model has also been developed for the perturbation observed in the excited vibrational state and to identify and predict many optically pumped FIR laser lines. The laser Stark study has provided accurate dipole moments and zero field transition frequencies in the ground state. Accurate molecular parameters are obtained for these isotopes. The interaction model was also applied in the case of a molecule with symmetric framework (ethane-D₃) to interpret the weak and complicated spectra in the three lowest torsional states and the molecular parameters were determined. These results will be useful for finding new emission lines with the optically pumped FIR laser being developed at CAT.

ACCELERATOR PROGRAMME

RF ion source

A radio frequency (RF) ion source has been developed for a 150 keV ion implantor. This ion source is capable of providing any gaseous ion. An indigeneously developed RF power source that operates at a frequency of 189.7 MHz has been used for this purpose.

The RF source consists of a quartz tube (44 mm diameter, 200 mm length) with a tungsten electrode fused at one end. The extraction potential is applied to this electrode. To prevent damage to this electrode from the electrons, a perforated quartz shield is provided. On the other end of the quartz tube an extraction port, having a highly polished aluminum canal with an aluminum collimator, is fixed. This assembly is housed in a stainless steel jacket which is insulated from it by a ceramic ring. The gas is fed into the source using a fine control needle valve. The RF power is transferred to the quartz tube by a capacitive coupling via an RF-matching network. The capacitance can be varied from 0 to 8 pF. Focusing of the ions at the extraction port is achieved by a solenoidal field.

Helium and argon ions have been extracted using this source in the pressure range 10⁻² to 10⁻⁵ mbar. The RF

Cover: Scanning electron micrograph showing surface topography of porous silicon.